

Uproc6

The progressive enduro king

Whether at an unbeatable pace on a challenging trail, ploughing through rock gardens or hitting jumps – the Uproc6 transforms the most extreme routes into a playground. While reason causes you to brake, courage and confidence propel you forwards and the Uproc6 leaves the impossible behind. The mullet concept with a 29-inch front wheel and a 27.5-inch rear wheel as well as a slack head tube angle guarantee a smooth ride and control, while the 170/160 mm of travel absorbs everything – except fun! Thanks to its short chainstays, the Uproc6 maintains its agility even on winding trails and enables proper carving in turns. The clever four-link suspension design with generously dimensioned bearings and specifically adapted rear shocks guarantees perfect control and combines dynamics with the stability and reserves of a downhill bike. The powerful Bosch Performance Line CX drive unit and the fully integrated high-capacity 625 Wh PowerTube battery provide a great deal of power and the charge required for endless descents. In addition to its technical sophistication and first-class riding performance, the Uproc6 also boasts exceptional and robust elegance with its sculpted carbon frame. The Uproc6 in a nutshell: uphill rocket; downhill rocker.



Uproc6 9.50
Black / Brown Gold Satin

The product images shown in this catalogue may differ from the specifications. Colours may differ.

Bosch Performance Line CX motor

The most powerful Bosch drive is particularly compact, yet still provides high levels of performance and efficiency. The Performance Line CX accelerates with power, reacts without delay and is impressive with its agile handling and enhanced control. With 85 Nm torque, perfectly dispensed assistance up to 340 % and dynamic response characteristics, the Performance Line CX takes e-biking pleasure to new heights.



Screwed-in battery

To ensure a particularly secure attachment, the fully integrated PowerTube battery is screwed into the frame with a bolt. This smart integration guarantees a completely secure, vibration-free fit of the battery, while simultaneously allowing the battery to be replaced in just a few steps with a 6 mm Allen key – even out on the trail. The correct Allen key is contained in the axle of the rear wheel.



Full carbon frame

Powerful aesthetics meet performance: the use of high-strength carbon fibres optimises the rigidity of the frame to provide precise and dynamic handling. The highly responsive chassis with its four-link suspension design offers 160 mm of travel with good mid-stroke support. The rigid and clever construction of the rocker link and the large dimensions of the industrial bearings at the pivot points emphasise the bike's robust character and will survive the toughest enduro missions.





Uproc 6 8.70
Lichen Green / Black Satin



Uproc 6 6.50
Pulse Red / Mars Red Satin

The product images shown in this catalogue may differ from the specifications. Colours may differ.

29" / 27.5" wheels (mullet bike)

The Uproc 6 is designed as a mullet bike with differently sized wheels. The combination of the 29-inch front wheel and 27.5-inch rear wheel (mullet bike) offers the advantages of both wheel sizes: the best roll-over resistance and optimal grip thanks to the larger front wheel combined with the high level of agility and riding dynamics of the more compact rear wheel.



Progressive enduro frame geometry

The slack head tube angle and long reach guarantee an incredibly powerful and stable riding experience, even at high speeds. Thanks to its short chainstays, the Uproc 6 also boasts agility, dynamics and confident handling in curves. When riding uphill, the steep seat tube angle allows a central seating position and excellent climbing abilities. The low standover height increases freedom of movement and control on any terrain.



Components optimised for e-enduro use

Components that are consistently designed for hard enduro riding guarantee the best riding performance and the highest level of control on challenging terrain. The suspension fork with its generously dimensioned 38 mm stanchions and 170 mm of travel, for example, combines a high level of rigidity for precise steering with optimum suspension and shock absorption performance.



Uproc6

Prices in EUR – non-binding recommended retail price, including legal VAT

		Uproc6 6.50	Uproc6 8.70	Uproc6 9.50
		6999	8499	10999
Wheel size	29" / 27.5"	•	•	•
Frame shape	Full Suspension	•	•	•
Frame feature	FLYER Engineered, Carbon, 4-Link Suspension, 160 mm Travel, Integrated Battery	•	•	•
Frame material	Carbon	•	•	•
Frame details	Internal Cable Routing, Boost 12x148 mm	•	•	•
Frame size	S	▽	▽	▽
	M	▽	▽	▽
	L	▽	▽	▽
	XL	▽	▽	▽
Frame colour	Lichen Green/Black Satin	▽	▽	▽
	Pulse Red/Mars Red Satin	▽	▽	▽
	Black/Brown Gold Satin	▽	▽	▽
Rear shock	RockShox Deluxe Select R, 205x65mm Trunnion	•	–	–
	Fox DPX2 Performance, 205x65mm Trunnion	–	•	–
	Fox DPX2 Factory, 205x65mm Trunnion	–	–	•
Fork	RockShox ZEB, 170 mm, 15x110 mm Boost	•	–	–
	Fox 38 Performance Grip, 170 mm, 15x110 mm Boost	–	•	–
	Fox 38 Factory Grip2, 170 mm, 15x110 mm Boost	–	–	•
Motor	Bosch Performance Line CX	•	•	•
Assistance levels	4 assistance levels (including E-MTB mode)	•	•	•
Pedal assist	Up to 25km/h	•	•	•
Pushing aid	Pushing aid up to 6 km/h	•	•	•
Battery	Bosch PowerTube 625 (625Wh/16.7Ah/36V)	•	•	•
Display	Bosch Purion	•	•	•
	Bosch Kiox	150	150	150
Type of gears	Derailleur gears	•	•	•
Gears	SRAM NX Eagle, 12 speed, 11-50t	•	–	–
	Shimano XT, 12 speed, 10-51t	–	•	–
	SRAM X01 Eagle AXS, 12 Speed, 10-50t	–	–	•
Brakes	Shimano BR-MT520, 203/203mm	•	–	–
	Shimano XT BR-M8120, 203/203mm	–	•	–
	Magura MT7 HC3 Lever, 220/203mm	–	–	•
Stem	FLYER Alloy, 31.8x40 mm, 3°	•	•	–
	Spank Split, 31.8x38 mm, 0°	–	–	•
Handlebars	FLYER Alloy, 780 mm, 9°, 25 mm	•	•	–
	Spank Oozy Vibrocore, 780 mm, 9°, 25 mm	–	–	•
Saddle	Fizik Alpaca Terra	•	•	•
Seat post	FLYER Dropper Post MT171, 125 (S)/150 (M)/170 (L-XL) mm Travel, 34.9 mm	•	•	–
	SRAM Reverb AXS, 125 (S)/150 (M)/170 (L-XL) mm Travel, 34.9 mm	–	–	•
Rims	DT Swiss H 1900 Spline 30	•	–	–
	DT Swiss H 1700 Spline 30	–	•	–
	DT Swiss HX 1501 Spline 30	–	–	•
Tyres	Front: Maxxis Assegai DD 29x2.50/Rear: Maxxis Minion DHF DD 27.5x2.50	•	•	•
Pedals	VP 532	•	•	•
Headlight	Without Headlight	•	•	•
Charger	Bosch Fast Charger 6A	•	•	•

Weight without battery: about 20.9kg, Weight battery: about 3.5kg, Weight of bike with battery: about 25kg, Permitted total weight: 130kg