

# GOROC 2

## THE SUV BIKE

**Power, versatility, stability – the Goroc2 has everything that a genuine high-performance all-rounder needs. Its robust construction lends the crossover e-bike genuine SUV qualities – both in urban traffic and on bumpier terrain outside of town.**

29-inch wheel sets with substantial 2.6-inch all-terrain tires keep the rolling resistance low and provide excellent levels of comfort, safety, and

traction both on and off-road. The sleek design and high torsion resistance of the oversize aluminum frame with a 1.8-inch head tube produces a comfortable, robust ride. Smart details such as the internally routed cables and the speed sensor integrated into the frame produce a clean aesthetic and highlight its premium character.

**6.30 HS**  
Cast Silver /  
Black Gloss



**45**KM/H  
HIGH-SPEED OPTION

## Panasonic GX Ultimate Pro FIT

95 Nm torque means no climb is too steep

## Oversize aluminum frame

Incredible riding stability and a muscular aesthetic

## 750-Wh battery

Plenty of energy for extended tours

The FIT 2.0 control elements combine intuitive operation, readability, a smartphone connection, and innovative functions into a single intelligent system. A larger «FIT Display Comfort» display can be fitted later if required. The fully integrated 750 Wh battery is easy to remove laterally for external charging. The sporty yet

comfortable seating position and 120 mm suspension forks ensure comfort and ride safety on a wide range of terrains. Even with high loads, the powerful motor and permissible total weight up to 150 kg ensure a smooth, stable ride.

## GOROC2

		2.10	6.30	6.30 HS
Wheel size	29"	●	●	●
Frame shape	Comfort	○	○	○
	Gents	○	○	○
Frame	Aluminium   FLYER engineered, hydroformed tubing   Internal cable routing, Boost 12 x 148 mm	●	●	●
Frame size	S / M / L / XL	○	○	○
Frame colour	Cast Silver / Black Gloss	○	○	○
	Coast Blue / Black Matt	○	○	○
	Mercury Red / Black Gloss	○	○	○
Fork	SR Suntour XCR34 Air, 120 mm travel, 1.8" steerer, 15 x 110 mm Boost	●	-	-
	SR Suntour Zeron35 Air, 120 mm travel, 1.8" steerer, 15 x 110 mm Boost	-	●	●
Motor	Panasonic GX Ultimate Pro FIT	●	●	●
Pedal assist	up to 25 km/h	●	●	-
	up to 45 km/h	-	-	●
Battery	FLYER FIB-750 36V FIT (750 Wh / 20.1 Ah / 36 V)	●	●	●
Display	FIT Display Compact (DSP1-M, 2" color display)	●	●	●
Gears	Shimano Deore, 10 speed, 11-46t	●	-	-
	Shimano XT/Deore, 12 speed, 10-51t	-	●	●
Brakes	Shimano MT420, 203/180 mm	●	-	-
	Shimano MT520, 203/180 mm	-	●	-
	Magura MT5e, 203/180 mm	-	-	●
Stem	FLYER alloy, 35 x 50 mm, 0°	●	●	●
Handlebars	FLYER alloy, 740 mm, 7°, 25 mm	●	●	●
Saddle	Selle Royal Essenza+	●	●	●
Seat post	FLYER Alloy, 31.6 x 300 (S-M) / 350 (L-XL) mm	●	●	●
Rims:	Alexrims MD30	●	●	●
Front hub:	Formula DC-511, 32h	●	●	●
Rear hub:	Formula EHL-148S, 32h	●	-	-
	Formula EHL-148M, 32h	-	●	●
Tyres	Schwalbe Johnny Watts 29 x 2.60 (65-622)	●	●	●
Pedals	VP 527	●	●	●
Headlight	Supernova MINI 2	●	-	-
	Supernova M99 Mini Pure 25	-	●	-
	Supernova M99 Mini Pure 45	-	-	●
Rear light	Busch & Müller 2C	●	●	-
	Supernova M99 Tail Light 45	-	-	●
Mudguard	SunnyWheel 65mm	●	●	●
Kickstand	Pletscher Comp Flex	●	●	●
Rack	FLYER Racktime, integrated spring flap	●	●	●
Rearview mirror	With rearview mirror	-	-	●
Registration plate holder	With registration plate holder	-	-	●
Anti-theft protection	Abus battery lock with YourPlus one key system	●	●	●
Charger	FIT Fast Charger 36V 6A	●	●	●

Weight without battery approx. **25,5 Kg** | Weight of battery approx. **4,3 Kg** | Weight ready to drive approx. **30 Kg** | Permissible total weight approx. **150 (HS 149) Kg**

● Standard specification | - not available | ○ free option | (C) Comfort | (M) Mixed | (G) Gents

GOROC2

# THE SUV BIKE

**2.10**

Cast Silver /  
Black Gloss



**6.30 HS**

Coast Blue /  
Black Gloss



**6.30**

Mercury Red /  
Black Gloss



# GEOMETRY

## GENTS

cm	S 160-170	M 170-180	L 180-190	XL 190-200
A	400	450	500	550
B	604	620	649	682
C	118	128	138	148
D	505	505	505	505
E	69°	70°	70.5°	70.5°
F	73°	73°	73°	73°
G	65	65	65	65
M	315	315	315	315
I	1179	1184	1207	1240
J	760	785	800	830
K	673	687	699	708
L	398	410	435	465
M	1938	1943	1966	1999

## COMFORT

cm	S 160-170	M 170-180	L 180-190	XL 190-200
A	400	450	500	550
B	604	620	649	682
C	118	128	138	148
D	505	505	505	505
E	69°	70°	70.5°	70.5°
F	73°	73°	73°	73°
G	65	65	65	65
M	315	315	315	315
I	1179	1184	1207	1240
J	700	700	700	700
K	673	687	699	708
L	398	410	435	465
M	1938	1943	1966	1999

A	Seat tube length
B	Top tube length
C	Head tube length
D	Chainstay length
E	Head tube angle
F	Seat tube angle
G	Bottom bracket drop
M	Bottom bracket height
I	Wheelbase
J	Protrusion height/clearance height
K	Stack
L	Reach
M	Total length