

UPROC6

THE ENDURO BENCHMARK

The Uproc6 is perfectly geared towards downhill performance. Enduro riders looking for maximum fun and downhill performance can make almost anywhere their playground on the Uproc6 – with no aerial cableway, shuttles, or tired legs. Downhill rocker or uphill rocket? Both!

The four-link suspension design with enduro-adapted rear shocks guarantees control and combines a dynamic ride with the stability and reserves of a downhill bike. The stiff carbon rocker link and the large industrial bearings at the pivot points are designed for the toughest uses.

9.50

Curcuma Gloss



**PREMIUM
CARBON
FRAME**

PROGRESSIVE STYLING,
PERFECTLY MADE

Additional enduro highlights include the suspension fork, with large 38 mm stanchions and 170 mm travel, «Maxxis Assegai / Minion DHF» tires with strengthened «Double Down» casing, robust hybrid wheel sets from DT Swiss and four-piston brakes with large brake discs (up to 220 mm). The high-strength carbon fiber frame is laminated to create a dynamic ride with perfect rigidity. The «Bosch Performance Line CX» drive with

high-end sensors and 85 Nm torque provides powerful assistance for the steepest trail passages. Plenty of energy for countless downhill comes from the fully integrated PowerTube battery with 625 Wh. The bolt-in battery attachment guarantees a completely secure, vibration-free fit of the battery, while simultaneously allowing it to be replaced in just a few steps with a 6 mm hex key – even out on the trail.

170/160 mm travel

Maximum riding performance and control for challenging downhill

Mixed Wheel concept (29"/27.5")

Excellent roll-over characteristics, grippy and agile

Progressive enduro geometry

Combines an extremely smooth, secure ride with agility

UPROCG

		6.50	8.70	9.50
Wheel size	29" / 27.5"	●	●	●
Frame	Carbon FLYER engineered, 4-link suspension, 160 mm travel Internal cable routing, Boost 12 x 148 mm	●	●	●
Frame size	S / M / L / XL	○	○	○
Frame colour	Anthracite Satin Curcuma Gloss	○	○	○
Rear shock	RockShox Deluxe Select R, 205 x 65 mm trunnion Fox Float X Performance, 205 x 65 Trunnion Fox Float X Factory, 205 x 65 Trunnion	● - -	- ● -	- - ●
Fork	RockShox ZEB, 170 mm travel, 15 x 110 mm Boost Fox 38 Float Performance, 170 mm travel, 15 x 110 mm Boost Fox 38 Float Factory, 170 mm travel, 15 x 110 mm Boost	● - -	- ● -	- - ●
Motor	Bosch Performance Line CX	●	●	●
Battery	Bosch PowerTube 625 (625 Wh / 17.4 Ah / 36 V)	●	●	●
Display	Bosch Kiox	●	●	●
Gears	Sram NX Eagle, 12 speed, 11-50t Shimano XT, 12 speed, 10-51t Sram X01 AXS, 12 speed, 10-50t	● - -	- ● -	- - ●
Brakes	Shimano MT520, 203/203 mm Shimano XT BR-M8120, 203/203 mm Magura MT7 HC3 lever, 220/203 mm	● - -	- ● -	- - ●
Stem	FLYER alloy, 31.8 x 40 mm, 3°	●	●	●
Handlebars	FLYER alloy, 780 mm, 9°, 25 mm	●	●	●
Saddle	Fizik Alpaca Terra	●	●	●
Seat post	FLYER dropper post MT214, 125 (S) / 150 (M) / 170 (L-XL) mm travel, 34.9 mm KS LEV Integra Remote, 125 (S) / 150 (M) / 175 (L-XL) mm travel, 34.9 mm Sram Reverb AXS, 100 (S) / 125 (M) / 150 (L-XL) mm travel, 34.9 mm	● - -	- ● -	- - ●
Wheels	DT Swiss H 1900 Spline 30 DT Swiss H 1700 Spline 30 DT Swiss HX 1501 Spline 30	● - -	- ● -	- - ●
Tyres	Front: Maxxis Assegai 3C DD TR 29 x 2.50WT (63-622) / Rear: Maxxis Minion DHF 3C DD TR 27.5 x 2.50WT (63-584)	●	●	●
Pedals	VP 532	●	●	●
Charger	Bosch 6A fast charger	●	●	●

Weight without battery approx. **20,9 Kg** | Weight of battery approx. **3,5 Kg** | Weight ready to drive approx. **25 Kg** | Permissible total weight approx. **140 Kg**

● Standard specification | - not available | ○ free option | (C) Comfort | (M) Mixed | (G) Gents

UPROC6

THE ENDURO BENCHMARK



6.50
Curcuma Gloss



8.70
Anthracite Satin

SHOCK ADJUSTMENT

UPROC6 6.50 ROCKSHOX DELUXE SELECT R, 205 X 65 MM TRUNNION

Rider weight Kg	Air pressure PSI	Rebound Clicks (10) from closed
50	105	9
55	120	8
60	135	8
65	145	8
70	160	7
75	170	7
80	185	6
85	195	5
90	210	4
95	220	4
100	235	3
105	245	3
110	260	2

UPROC6 8.70 FOX FLOAT X PERFORMANCE, 205 X 65 TRUNNION

Rider weight Kg	Air pressure PSI	Rebound Clicks (15) from closed
50	120	13
55	140	13
60	155	12
65	170	12
70	190	11
75	205	10
80	225	9
85	240	8
90	255	7
95	275	6
100	290	5
105	305	4
110	325	3

UPROC6 9.50 FOX FLOAT X FACTORY, 205 X 65 TRUNNION

Rider weight Kg	Air pressure PSI	Rebound Clicks (15) from closed
50	120	13
55	135	13
60	155	12
65	170	12
70	185	11
75	205	10
80	220	9
85	235	8
90	255	7
95	270	6
100	285	5
105	305	4
110	320	3

GEOMETRY

cm	S 160-170	M 170-180	L 180-190	XL 190-200
A	395	415	450	485
B	579	608	636	664
C	100	100	105	110
D	445	445	445	445
E	63.5°	64.5°	64.5°	64.5°
F	75.7°	75.5°	75.3°	75.2°
G	31	31	31	31
M	347	347	347	347
I	1208	1223	1250	1277
J	756	753	756	758
K	623	629	633	638
L	420	445	470	495
M	1937	1952	1979	2006

A	Seat tube length
B	Top tube length
C	Head tube length
D	Chainstay length
E	Head tube angle
F	Seat tube angle
G	Bottom bracket drop
M	Bottom bracket height
I	Wheelbase
J	Protrusion height/clearance height
K	Stack
L	Reach
M	Total length